

Product Name	NX 2080 PU Flock
Product Description	Soft and elastic ready-made transparent printing paste with high covering performance, specially developed for flock adhesion printing.
Properties and Application Areas	<ul style="list-style-type: none"> <li>* It is a ready-made compact formulation based on water-based aliphatic polyurethane binder.</li> <li>* The prints made with this product are resistant to domestic type washing at 40°C. Adding <b>NXFix</b> up to 3% of the paste can increase washing fastness and resistance for tougher washing conditions.</li> <li>* Very good elasticity. Prints do not lose their flexibility even with multiple household washes at 40°C.</li> <li>* Complies with ecological requirements, does not contain harmful components. It does not contain formaldehyde.</li> <li>* Compatible with all <b>NX</b> series printing auxiliaries.</li> </ul>
<b>General Properties</b>	
Chemical Composition	: Transparent compact paste of water-based aliphatic polyurethane binders, thickeners and crosslinking agents.
Ionicity	: Anionic
Appearance	: Semi transparent viscous paste.
pH (at 20°C)	: 7.5 (+, - 0.5)
<b>Application Information</b>	
Printing Applications	<ul style="list-style-type: none"> <li>* Stir the product before use.</li> <li>* Product is suitable for single layer printing.</li> <li>* Working with printing templates of 43-62 mesh range is recommended.</li> <li>* Use 55 to 65 Shore hardness and U type squeegee.</li> <li>* In order to reduce the viscosity of the printing paste, <b>NX 2000 PU Regulator</b> should be added between 1% to 3% of the paste. Do not add water to the paste.</li> <li>* After the printing process is completed, prints should be cured for 90 seconds at a temperature between 150-160°C.</li> <li>* It is recommended to add 3% <b>NXFix Cool</b> to the paste for the fabrics sensitive to the high curing temperatures. When <b>NXFix Cool</b> used, cure the prints for 180-120 seconds at temperatures between 70-100°C.</li> <li>* If <b>NXFix Cool</b> used in the paste, it should be consumed within 8 hours, otherwise paste will be unusable.</li> </ul>
Coating Applications	<ul style="list-style-type: none"> <li>* <b>NX 2080 PU Flock</b> is also suitable for coating. Paste thinning, coloring and curing recommendations described in the Printing Applications section are the same.</li> <li>* Coating blade angle and distance or kiss-roll settings are made according to the desired coating thickness.</li> <li>* Not suitable for pulverized spray coating.</li> </ul>

Product Name	NX 2080 PU Flock
<b>Other Information</b>	
Shelf Life	6 months in closed containers from the date of production.
Safety Information	Handling, ecological compatibility and toxicological information of the product can be found in the product safety data sheet.
Disclaimer	<p>This information and our technical advice - whether verbal, in writing or by way of trials - are given in good faith but without warranty, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to check its validity and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with the current version of our General Conditions of Sale and Delivery.</p>